

| TYPE  | PART #   | TEMP.                         | DESCRIPTION  | LISTINGS      |
|---|--|-------------------------------|--|---------------|
| <b>DRYROD<sup>®</sup> PORTABLE OVENS</b>                |  |                               |  |               |
| <b>TYPE 1</b><br>10 lb (5 kg)                           | 1205500  | 300°F<br>(149°C)              | 100-240V AC/DC @ 60 watts with indicator light                 | ETL, cETL, CE |
| <b>TYPE 2</b><br>20 lb (10 kg)                          | 1205510  | 100° - 300°F<br>(38° - 149°C) | 100-240V AC/DC @ 70 watts with digital thermometer             | ETL, cETL, CE |
| <b>TYPE 5</b><br>50 lb (25 kg)                          | 1205522  | 100° - 300°F<br>(38° - 149°C) | 120/240V AC only @ 300 watts (With wheels)                     | UL, cUL, CE   |
|   | 1205520  |                               | Same as above with digital thermometer                         |               |
|   | 1205523  |                               | 120/240V AC only @ 300 watts (With handle)                     |               |
| 1205521   | Same as above with digital thermometer                         |                               |  |               |
| <b>TYPE 15</b><br>150 lb (70 kg)                        | 1205530  | 100° - 300°F<br>(38° - 149°C) | 120/240V AC only @ 600 watts with digital thermometer          | UL, cUL, CE   |
| <b>DRYROD<sup>®</sup> BENCH OVENS</b>                   |  |                               |  |               |
| <b>TYPE 15B</b><br>150 lb (70 kg)                       | 1205531  | 100° - 300°F<br>(38° - 149°C) | 120/240V AC only @ 600 watts with digital thermometer          | UL, cUL, CE   |
| <b>TYPE 300</b><br>400 lb (181 kg)                      | 1200200  | 100° - 550°F<br>(38° - 288°C) | 120/240V AC only @ 1000 watts                                  | ETL, cETL, CE |
|   | 1200201  |                               | 120/240V AC only @ 1000 watts with thermometer                 |               |
|   | 1200203  |                               | 120/240V AC only @ 1000 watts with thermometer & stacking lugs |               |
|   | 1200101  |                               | 240/480V AC only @ 1000 watts with thermometer                 |               |
| 1200103   | 240/480V AC only @ 1000 watts with thermometer & stacking lugs |                               |  |               |
| <b>TYPE 900</b><br>1100 lb (500 kg)                     | 1200301  | 100° - 550°F<br>(38° - 288°C) | 240/480V @ 2400 watts single phase with thermometer            | CE            |
| <b>DRYROD<sup>®</sup> HIGH TEMPERATURE BENCH OVENS</b>  |  |                               |  |               |
| <b>TYPE 200HT</b><br>200 lb (90 kg)                     | 1200461  | 100° - 550°F<br>(38° - 288°C) | 120/240V AC only @ 1000 watts with thermometer                 | N/A           |
| <b>TYPE 300HT</b><br>400 lb (181 kg)                    | 1200161  | 100° - 660°F<br>(38° - 350°C) | 120/240V AC only @ 1500 watts with digital thermometer         | N/A           |
| <b>TYPE 900HT</b><br>1100 lb (500 kg)                   | 1200361  | 100° - 660°F<br>(38° - 350°C) | 120/240V AC only @ 4000 watts with digital thermometer         | N/A           |
| <b>DRYROD<sup>®</sup> REBAKING/RECONDITIONING OVENS</b> |  |                               |  |               |
| <b>TYPE 40HT</b><br>400 lb (181 kg)                     | 1204402  | 100° - 800°F<br>(38° - 427°C) | 1/240V @ 4500 watts  | N/A           |
|   | 1204400  |                               | 3/480V @ 4500 watts  |               |
| <b>DRYROD<sup>®</sup> FLUX OVENS</b>                    |  |                               |  |               |
| <b>Type 250FX</b><br>250 lb (113 kg)                    | 1201920  | 100° - 750°F<br>(38° - 399°C) | 220V AC @ 3000 watts   | CE            |
| <b>DRYWIRE<sup>®</sup> FCW OVENS</b>                    |  |                               |  |               |
| <b>TYPE 4</b>   | 1205438  | 100° - 300°F<br>(38° - 149°C) | 120/240V AC @ 1000 watts single phase with digital thermometer | N/A           |
| <b>TYPE 24</b>  | 1205431  | 100° - 550°F<br>(38° - 288°C) | 240/480V AC @ 2500 watts single phase with thermometer         | UL, cUL       |

\*cUL and cETL are approved to CSA standards